

## DEBASOFT NDLC

***APEO free degreasing agent for skins with high natural fat content. Especially effective on fatty skins.***

### Descriptive properties

<b>Composition</b>	: Aliphatic ethoxylated product
<b>Appearance</b>	: Colorless slightly viscous liquid
<b>pH</b>	: 7,0 - 8,0
<b>Stability</b>	: Very good to electrolytes, acids and alkalis. Good stability in hard water.
<b>Solubility</b>	: Gives clear solutions up to 60°C, can also be added undiluted to the float
<b>Storage</b>	: App. 2 years - dry storage-

Debasoft NDLC is an excellent and highly effective degreasing system that gives a natural and biologically acceptable fat emulsion in the effluent.

Debasoft NDLC with its optimum foaming, wetting, emulsifying, washing and cleaning performance shows substantially high fat uptake capacity and its characteristic flash foam imparts outstanding cleanness to hides and skins.

Debasoft NDLC has outstanding enzyme compatibility. As such we strongly recommend its combined use with enzymatic auxiliaries, especially with Debazym LP NEW.

Debasoft NDLC has a positive and synergistic effect when combined also with other anionic, nonionic and amphoteric surfactants.

Debasoft NDLC works perfectly even at low temperatures and does not necessitate high alkali conditions.

### Application recipes

**Highly recommended for all soaking, degreasing and washing floats.**

Soaking: 0,5 - 1,5 g/l

### Fur skins processes:

**Wool washing (1:20):** 1,0 - 2,5 g/l

**Degreasing in depickling float: (1:5-8):** 1,0 - 2,5 g/l

**Degreasing:** 6,0 - 8,0 g/l

### Remarks

The product may separate under extreme cold or warm storage conditions. Before use, mix by stirring, pump circulation or any other suitable method at 15 - 25°C.

### Packaging

120 kg in polyethylene drums or 1000 kg in IBC.

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.