

DEBASOFT FLT

Specialty for improved water resistance and touch.

Descriptive properties

Composition	:	Based on fluorocarbon resins free of PFOA
Appearance	:	Milky emulsion
Charge	:	Weakly cationic
Solubility in water	:	Emulsifiable with water
Stability	:	Not stable to acids, electrolytes, pickle and chrome liquors
Storage	:	Minimum 1 year - dry storage-

Debasoft FLT while improving water resistance imparts oil repellency and stain resistance without much changing the touch.

Debasoft FLT will improve dye shade and brilliancy.

Application recipes

Apply with spray gun without diluting.

Remarks

Protect from frost and high temperatures. For further information please refer to its MSDS.

Packaging

120 kg in polypropylene drums.

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.





İstanbul Deri Organize Sanayi Bölgesi Burçak Sokak No.: 2 VIII. Özel Parsel 34956 Tuzla - İstanbul / TÜRKİYE Phone: +90 216 394 00 70 • Fax: +90 216 394 16 97 • info@debagkimya.com • www.debagkimya.com