

ZDHC LEVEL 1
MRSL v2.0 Compliant
ZDHC LEVEL 1
MRSL v1.1 Compliant

EMDIRENAL RT3

General purpose lightfast polymer with high dispersing and stabilizing power to improve grain tightness, softness and fullness.

Descriptive properties

Composition : Acrylic copolymer
Appearance : Colorless liquid
pH (1:10) : 7,5 - 8,5
Solubility in water : Easily soluble

Storage : Minimum 1 year - dry storage-

Emdirenal RT3 has a wide range of applications but its most important characteristic is its stabilizing power: it improves and accelerates the distribution and penetration of anionic chemicals through the leather cross-section.

Leathers treated with Emdirenal RT3 show excellent grain tightness, softness and fullness with improved dye penetration and evenness even after buffing.

Emdirenal RT3 can also safely be used in chrome tanning and retanning to improve chrome exhaustion.

The use of Emdirenal RT3 in the production of waterproof full grain or nubuck leather is highly recommended.

Remarks

Please refer to its MSDS.

Packaging

150 kg in polypropylene drums.

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.

Certified to: ISO 9001: 2015 ISO 14001: 2015 ISO 45001: 2018

